

Fire Fighting Trailers

Mainstream Monitor Trailer

Description

Orion Mainstream trailers are highly mobile small trailer mounted monitors. The most standard model uses an 80mm (3") Warden monitor. The trailers include a flat deck for the operator to stand on. Monitors may be rotated through 360 degrees. The trailers are fitted with a water manifold with the appropriate number of inlets for connection to the water supply

Trailers are equipped with stabilising legs on all four corners and an adjustable jockey wheel.



Mainstream Trailer with Warden 8095 monitor and FF-2000PB foam nozzle

ORION FIRE ENGINEERING PTY LIMITED

ABN 80 002 538 696

26A LYN PARADE PRESTONS NSW 2170 AUSTRALIA

Tel (61) 2 9426 7900 FAX (61) 2 8783 5400

Visit our Website www.orion-fire.com.au Email: sales@orion-fire.com.au

Specifications

Trailer will be supplied with the following:

- ½ tonne axle with overrun brakes
- 50mm ball hitch c/w hand brake
- Hot dipped galvanised trailer and waterway
- Aluminium checker plate flat bed
- Aluminium hose box (for 17 hoses)
- Retractable legs (4 off) at each corner
- Retractable Jockey Wheel
- 100mm Cast Iron Gate Valve
- 15" Tyres
- ADR Approved 3 in 1 brake lights
- Water inlets 4 x 65mm BSP Female, c/w brass check valves trailer and checker plate floor painted as per paint specification
- Warden 8090 monitor
- FF-4000PSD foam nozzle with metering valve

Options

- Monitor geared (shown)
- Water inlet(s) fitted with check valves
- Road lighting to most international standards
- Screw down jacks
- Spare tyre
- Equipment boxes
- Customised paint systems
- Choice of vehicle tow connection

ORION FIRE ENGINEERING PTY LIMITED

ABN 80 002 538 696

26A LYN PARADE PRESTONS NSW 2170 AUSTRALIA

Tel (61) 2 9426 7900 FAX (61) 2 8783 5400

Visit our Website www.orion-fire.com.au Email: sales@orion-fire.com.au