Handline Nozzles

Industrial Fog Nozzles

Fire Engineering
Pty Limited

Description

The Orion Series 'A' industrial fog nozzles are high quality, near constant flow nozzles with features unmatched by the available alternatives.

- Available in gunmetal, nickel plated as an option
- Available in 316 SS (minimum order quantities apply)
- Nearly constant flow from straight stream to full fog.
- Rubber bumper (A-20, A-25 and A-40).
- High flow rates.
- Twist shut-off

A-25 A-40 A-50

A-20

The A-20 is a hose reel nozzle and is supplied with a 20mm female base thread and a rubber bumper. Two flow rates are available 50 lpm and 100 lpm at 700 kPa.

Length: 82mm Diameter: 50mm Range (Straight Stream): 26M

A-25

The A-25 is a hose reel nozzle for 25mm hoses and is supplied with a 25mm female base thread or 40mm female thread and a rubber bumper. Two flow rates are available 50 lpm and 100 lpm at 700 kPa.

Length: 82mm Diameter: 50mm Range (Straight Stream): 26M

A-40

The A-40 is a hose nozzle for 38mm hoses and is supplied with a 40mm female base thread. Flow rates are 300, 400 & 500 lpm at 700 kPa.

Length: 100mm Diameter: 66mm Range (Straight Stream): 32M

A-50

The A-50 is a hose nozzle for 65mm hoses and is supplied with a 40mm female base thread. Flow rates are 600, 800 & 1000 lpm at 700 kPa. The standard flow rate is 1000 lpm.

Length: 117mm Diameter: 62mm Range (Straight Stream): 45M

ORION FIRE ENGINEERING PTY LIMITED
ABN 80 002 538 696
26A LYN PARADE PRESTONS NSW 2170 AUSTRALIA
Tel (61) 2 9426 7900 FAX (61) 2 8783 5400
Visit our Website www.orion-fire.com.au Email: sales@orion-fire.com.au