HANDLINE FOAM BRANCHPIPES

Fire Engineering
Pty Limited

DESCRIPTION.

The Orion FOAM FORCE FF-XXX foam branchpipes are compact, light weight nozzles with excellent foam making qualities and excellent foam throw. The size of the nozzles allows them to be readily stored in normal fire hose cabinets and in apparatus lockers. A number of options are available to ensure that FOAMFORCE nozzles will meet the needs of most users. They can be used with pick up tube or with line proportioners to match their flow (225 lpm or 450 lpm). The FF-260P complies with AS 1940:2004 flow requirements.

SPECIFICATION.

	FF-230P	FF-260P * new	FF-450P
Flow Rate @ 500 kPa:	230 lpm	260 lpm	450 lpm
Proportioning Rate:	fixed at 3% or 6%	fixed at 3% or 6%	fixed at 3% or 6%
Length (excluding coupling):	410 mm	410 mm	410 mm
Weight (alloy):	1 kg	1 kg	1 kg
(brass)	3 kg	3 kg	3 kg
Pick-up tube length:	1.5 Meters	1.5 Meters	1.5 Meters
Throw @ 400 kPa	17 Meters	17.5 Meters	22 Meters
@ 700 kPa	21 Meters	22 Meters	25 Meters

MODELS / CONSTRUCTION.

FF-230PA, FF-260PA and FF-450PA. All aluminium construction, anodised.

OPTIONS.

- Branchpipes can be fitted with your choice of coupling.
- Variable or Fixed Line Proportioners to match.
- Special Flow Rates

ORION FIRE ENGINEERING PTY LIMITED
ABN 80 002 538 696
26A LYN PARADE PRESTONS NSW 2170 AUSTRALIA
Tel (61) 2 9426 7900 FAX (61) 2 8783 5400
Visit our Website www.orion-fire.com.au Email: sales@orion-fire.com.au