

# Hand Held Equipment



Fire Engineering  
Pty Limited

## Foam Mobile Unit FT-120

### Description

The Orion FT-120 Foam Mobile Unit has been designed for rapid deployment of foam extinguishing agent. The unit requires only a connection to a suitable water supply. Large diameter pneumatic tyres are fitted to the front.

Two hoses can be carried on the FT-120, one 30 metre length of 38mm hose and a 15 metre length of 65mm hose.

The standard unit comprises of the following features:

- 40mm Line proportioner c/w check valve fitted.
- Model FF-230A light alloy foam nozzle.
- Large 150mm Fill cap installed for easy filling.
- Approximate running time
  - using 3% foam 17 - 18 minutes
  - using 6% foam 8 - 9 minutes.



### Specifications

	Materials Construction	Of	Coating	Colour
Tank	Fibreglass		Nil	Red
Axle	Stainless Steel		None	
Handle & frame	Steel		Epoxy Paint	Black
Proportioner	Bronze (LG2)		Nil	Natural
Tyres	Rubber		Nil	Tyre – Black Hub – Red
Nozzle	Light Weight Aluminium		Body – Hard Anodised	

### Dimensions

Height:	850mm
Width:	700mm
Length:	1100mm
Weight (empty):	50kg

---

## ORION FIRE ENGINEERING PTY LIMITED

ABN 80 002 538 696

26A LYN PARADE PRESTONS NSW 2170 AUSTRALIA

Tel (61) 2 9426 7900 FAX (61) 2 8783 5400

Visit our Website [www.orion-fire.com.au](http://www.orion-fire.com.au) Email: [sales@orion-fire.com.au](mailto:sales@orion-fire.com.au)